


圓型端子

Ring Terminals

(R-type:Non-Insulated)



Unit:mm


ITEM NO.	φ d2	B	T	AWG	DINmm ²
R0.5-2	2.2	5.2			
R0.5-3	3.2	5.2	0.5	26-22	0.14-0.36
R0.5-4	4.3	6.6			
R0.5-5	5.3	8.0			
R1.25-3S	3.2	5.5			
R1.25-3	3.7	5.5			
R1.25-3M	3.7	6.6			
R1.25-4M	4.3	6.6			
R1.25-4	4.3	8.0	0.8	22-18	0.5-1.0
R1.25-5	5.3	8.0			
R1.25-6	6.4	11.6			
R1.25-8	8.4	11.6			
R1.25-10	10.5	13.6			
R1.25-12	13.0	19.0			
R2-3S	3.2	5.5			
R2-3	3.7	8.5			
R2-3M	3.7	6.6			
R2-4M	4.3	6.6			
R2-4	4.3	8.5	0.8	16-14	1.5-2.5
R2-5	5.3	9.5			
R2-6	6.4	11.6			
R2-8	8.4	11.6			
R2-10	10.5	13.6			
R2-12	13.0	19.0			
R3.5-3S	3.7	7.0			
R3.5-4S	4.3	7.0			
R3.5-4	4.3	8.0			
R3.5-5	5.3	8.0	1.0	14-12	2.5-4
R3.5-6	6.4	12.0			
R3.5-8	8.4	15.0			
R3.5-10	10.5	15.0			
R3.5-12	13.0	19.0			
R5.5-3S	3.7	7.2			
R5.5-4S	4.3	7.2	1.0	12-10	4-6
R5.5-4	4.3	9.5			
R5.5-5	5.3	9.5			

ITEM NO.	φ d2	B	T	AWG	DINmm ²
R5.5-6	6.4	12.0			
R5.5-8	8.4	15.0	1.0	12-10	4-6
R5.5-10	10.5	15.0			
R5.5-12	13.0	19.0			
R8-4NK	4.3	9.0			
R8-5NK	5.3	9.0			
R8-4S	4.3	9.0			
R8-4	4.3	12.0			
R8-5S	5.3	9.0			
R8-5	5.3	12.0			
R8-6	6.4	12.0	1.2	8	10
R8-6L	6.4	15.0			
R8-8	8.4	15.0			
R8-10	10.5	15.0			
R8-12	13.0	19.0			
R8-14	15.0	30.0			
R8-16	17.0	30.0			
R8-20	21.0	30.0			
R14-4	4.3	12.0			
R14-5S	5.3	9.5			
R14-5	5.3	12.0			
R14-6	6.4	12.0			
R14-8	8.4	16.0			
R14-10	10.5	16.0	1.5	6	16
R14-11	11.5	22.0			
R14-12	13.0	22.0			
R14-14	15.0	30.0			
R14-16	17.0	30.0			
R14-20	21.0	30.0			
R22-5S	5.3	12.0			
R22-6S	6.4	12.0			
R22-8S	8.4	12.0			
R22-5	5.3	16.5	1.8	4	25
R22-6	6.4	16.5			
R22-8	8.4	16.5			
R22-10S	10.5	16.5			

圓型端子

Ring Terminals

(R-type:Non-Insulated)



Unit:mm


ITEM NO.	φ d2	B	T	AWG	DINmm ²
R22-10	10.5	17.5			
R22-12	13.0	22.0			
R22-14	15.0	30.0	1.8	4	25
R22-16	17.0	30.0			
R22-18	19.0	30.0			
R22-20	21.0	30.0			
R38-5S	5.3	15.3			
R38-6S	6.4	15.3			
R38-8S	8.4	15.3			
R38-10S	10.5	15.3			
R38-6	6.4	22.0			
R38-8	8.4	22.0	1.8	2	35
R38-10	10.5	22.0			
R38-12	13.0	22.0			
R38-14	15.0	30.0			
R38-16	17.0	30.0			
R38-18	19.0	30.0			
R38-20	21.0	30.0			
R60-6	6.4				
R60-8	8.4				
R60-10	10.5	22.0	2.0	1/0	50
R60-11	11.5				
R60-12	13.0				
R60-14	15.0				
R60-16	17.0				
R60-18	19.0	32.0	2.0	1/0	50
R60-20	21.0				
R60-22	23.0				
R70-6	6.4				
R70-8	8.4				
R70-10	10.5	24.0	2.0	2/0	70
R70-11	11.5				
R70-12	13.0				
R70-14	15.0				
R70-16	17.0	32.0	2.0	2/0	70
R70-18	19.0				

ITEM NO.	φ d2	B	T	AWG	DINmm ²
R70-20	21.0	32.0	2.0	2/0	70
R70-22	23.0				
R80-6	6.4				
R80-8	8.4	27.0	2.3	3/0	95
R80-10	10.5				
R80-12	13.0				
R80-8L	8.4				
R80-10L	10.5				
R80-12L	13.0				
R80-14	15.0	32.0	2.3	3/0	95
R80-16	17.0				
R80-18	19.0				
R80-20	21.0				
R80-22	23.0				
R100-6	6.4				
R100-8	8.4				
R100-10	10.5	28.5	2.6	4/0	120
R100-11	11.5				
R100-12	13.0				
R100-8L	8.4				
R100-10L	10.5				
R100-12L	13.0				
R100-14	15.0	32.0	2.6	4/0	120
R100-16	17.0				
R100-18	19.0				
R100-20	21.0				
R100-22	23.0				
R150-6	6.4				
R150-8	8.4				
R150-10	10.5				
R150-12	13.0	36.0	3.2	250-300	150
R150-14	15.0			mcm	
R150-16	17.0				
R150-8L	8.4				
R150-10L	10.5				
R150-12L	13.0				

圓型端子

Ring Terminals

(R-type:Non-Insulated)



Unit:mm

ITEM NO.	φ d2	B	T	AWG	DINmm ²
R150-16L	17.0				
R150-18	19.0				
R150-20	21.0	36.0	3.2	250-300	150
R150-22	23.0			mcm	
R150-24	25.0				
R180-8	8.4				
R180-10	10.5				
R180-12	13.0				
R180-14	15.0				
R180-16	17.0				
R180-8L	8.4				
R180-10L	10.5	38.5	3.5	300-350	185
R180-12L	13.0			mcm	
R180-16L	17.0				
R180-18	19.0				
R180-20	21.0				
R180-22	23.0				
R180-24	25.0				
R180-27	28.0				
R200-8	8.4				
R200-10	10.5				
R200-11	11.5				
R200-12	13.0				
R200-14	15.0				
R200-16	17.0				
R200-8L	8.4				
R200-10L	10.5	44.0	4.0	400-450	240
R200-12L	13.0			mcm	
R200-14L	15.0				
R200-16L	17.0				
R200-18	19.0				
R200-20	21.0				
R200-22	23.0				
R200-24	25.0				
R200-27	28.0				

ITEM NO.	φ d2	B	T	AWG	DINmm ²
R325-8	8.4				
R325-10	10.5				
R325-12	13.0				
R325-14	15.0				
R325-16	17.0				
R325-8L	8.4				
R325-10L	10.5	50.0	4.5	500-600	300
R325-12L	13.0			mcm	
R325-14L	15.0				
R325-16L	17.0				
R325-18	19.0				
R325-20	21.0				
R325-22	23.0				
R325-24	25.0				
R325-27	28.0				